Space Interferometry Mission

Microarcsecond Precision Astrometry

S.C. Unwin (Jet Propulsion Laboratory, California Institute of Technology) unwin@huey.jpl.nasa.gov

What is SIM ?


SIM is NASA's first space-based long-baseline interferometer designed for precision astrometry. SIM will extend the reach of precision astrometry or cover the entire Galaxy, and will address a deverse set of topics in sellar astrophysics and Galactic astronomy, and will be an extraordinary toof for discovering planes. The principal science topics for SIM include

- Astrometric search for planets with masses as small as a few Earth masses around the nearest star
 Characterization of planetary systems: mass distribution; planet frequency; multi-planet systems
- . Calibration of the cosmic distance scale using Cepheids and other indicators
- Stellar Dynamics of the Galaxy
 Accurate masses for sub-stellar companions
 Orbits of globular clusters an satellite galaxies
- Dynamics and evolution of binary star
- · Rotational parallaxes to spiral galaxie
- . Dynamics of the local univers

SIM is being developed by NASA's Jet Propulsion Laboratory, a division of the California Institute of Technology. The mission is currently in Formulation Phase ('Phase A/B'). Implementation Phase will start in 2002, with launch expected in mid-2006. In October 1999, the Project selected one of two major architectures ideration for the SIM design. JPL is now busy developing this design in more detail, in partnership

The SIM Instrument

SIM comprises three Michelson interferometers on a 10-m structure. Collectors at each end of the structure contain afocal telescopes which compress the input beam from a diameter of 0.3 m. Two telescope pairs observe bright guide stars, to stabilize the optical system, and a third pair observes the science target. The instrument will be launched into an Earth-trailing solar orbit (like SIRTF)



The CCD camera on SIM is designed to detect the exact position of the white-light envelope of the interference fringes between the two 31-me entrance apartures. A laser metavlogy system measures the internal delay — the optical path of ference (OPP) between the two arms of the instrument. This internal fermines are the second of the optical path of the optical pat delay, measured repeatedly over the 5-year mission, allows us to calculate the 5 basic astrometric parameters of each target star. Position (RA and dec): proper motion (in RA and dec); and parallax.

SIM Observing Modes

Global astrometry

SIM will achieve an accuracy of 4 microarcseconds in absolute position for stars as faint as 20 magnitude. It will set up and maintain an astrometric grid (see below) of approximately 3000 stars down to about 12 mag, as a reference system for astrometry of science targets.

Narrow-angle (local) Astrometry

In this more, the instrument measures relative positions between the target star and several reference stars within a radius of 0.5 deg. These nearby stars define a tocal reference in which the 5th accuracy will be Interoarceson in a 1-hour observation, cycling between target and references stars.

Aperture Synthesis Imaging

SIM operance as an aperance synthesis imager, provide a fully diffraction linked aperance of 10m in the foreign data. The mission is required to demonstrate this capability for future imaging missions, such as the ferrestrial Planner Finder (TPF). Dy totating the intument, the (w.) vocatege with allow SIM to make 19-milliarses resolution images of enlawly coverage and the provided that the state of the provided of the provi imaging the line-emitting gas, SIM will measure the mass distribution in the nucleus.

Fringe Nulling

Fringo Numny

This capability is as chaology demonstration for a the Terrestrial Planet Finder. In milling mode, the light paths through the instrument are adjusted to place a dark fitney for 'nal') on the detector. This cancels most of the light from the bright central star, allowing off-rais light from a planet close to the star to be detected. SIM will be required to demonstrate on-axis suppression on a bright star, so a keed of 1 part in 10°.



Artist's impression of SIM in Earth-trailing solar orbi

Performance Summary

Wide Angle astrometric accuracy (1-D, 1-o) Narrow Angle astrometric accuracy (1-D, 1-a) Instrument Field of Regard

Synthesis Imaging resolution Aperture plane (u.v.) coverage, evenly distributed 4 μas (end of 5-yr mission) l µas (in I hour) 15 deg 7.3 µas in 50 minute

10 mas (at 0.7 µm)


SIM Astrometric Grid

SIM global astrometry requires an alt-sky reference grid, to which positions of target objects are referenced. SIM observes and maintains this grid by observing a set of overlapping 'tiles', akin to a plate survey. The major parameters of the grid are:

Number of reference stars

Estimated number of quasars Average number of stars per tile Average number of (1-D) visits V < 12 4 microarcsec RMS in RA and dec at end of 5 year mission 50 (tie to inertial frame)


astrophysical selection will be metal-poor K-III giants, at 1-4 kpc distance. The hardest requirement is the climination of perturbations due to binary companions: 4 microarcseconds requires eliminating not only stellar companions, but also sub-stellar companions below the brown-dwarf mass range.



Searching for Planets

One of SIM's primary scientific goals is the detection of low-mass planets around nearby stars. SIM will be the only instrument for the foreseeable future capable of approaching Earth-sized planets. The figure below shows the 'search space' of planet mass vs. planet orbital radius. SIM is complementary to the current techniques using stellar spectroscopy measurement of radial velocity. RV is more sensitive to short-period planets. SIM's astrometric method is more sensitive to long-period planets.

SIM will detect many new planets, and will obtain full orbital parameters for the multiple-planet systems



Search space for planet mass vs. planet orbital radius. Known planets are indicated as lower limits (due to the sin i ambiguity). Curves show the current radial velocity capability (10 m/s), and the astrometric sensitivity of the Keck Interferometer SIM and SIM. Note the large region of this parameter space which SIM can explore.

Research Opportunities with SIM

SMI Preparatory Science Program

Awards from the second year of the Preparatory Science Program (a NASA Research Announcement) were recently announced. This NRA was focused primarily on selection of stars for the SIM astrometric grid. NASA expects to issue a NRA for a third year, in late 2000

A third Mitchelson Summer School on Interferonectry will be held in Berkeley, California, August 21-25, 2000. Details will be available on the SIM web site. As in previous years, students and researchers new to the field will action a solid base in the principles and applications of optical and infrared interferometry. Matternals from

http://sim.jpl.nasa.gov/michelson/viewgraphs.html

Michelson Fellowship Program

Ellowships are direct annually to young researchers with the goal of developing expertise in optical interferonerty and its attrophysical applications. Gindutes makes fellowships support sudents at US universities and research intenticates of or three years. Newtocorte Fellowships are awarded normally for two years with an extension to three years. Application details are available on the SIM web size.

For More Information on SIM

- . Pick up a conv of the book "Space Interferometry Mission Taking the Measure of the Universe" is
- Pick up a copy of the SIM Science Working Group's (SIMSWG) Final Report (February 2000). SIMSWG was chartered by NASA to explore the fundamental science enabled by SIM's microarest precision. The Report describes the wide-ranging science impact of SIM.
- Sign up (on the web site) for the STM. News Letter distributed by e-mail about every 2 months.